

GEHR PP[®]

| 1. Manufacturer | | |
|-------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|
| | GEHR GmbH Casterfeldstraße 172 68219 Mannheim Deutschland Tel. +49 621 8789-0 Fax +49 621 8789-200 Info@gehr.de www.gehr.de | |
| 2. Product description | | |
| Article: | Engineering semi-finished product | |
| Abbreviation | PP-H | |
| Material characterisation | Thermoplastics | |
| Main components | Polypropylene-Homopolymerisate, contains event. pigments, stabilizers and additives | |
| Marking obligation components | none | |
| | | |
| Classification according REACh | Product | |
| Classification according REACh 3. Product properties | Product | |
| | Product Rods, sheets, profiles / solid | - |
| 3. Product properties | | - |
| 3. Product properties Form / condition | Rods, sheets, profiles / solid | |
| 3. Product properties Form / condition Colour | Rods, sheets, profiles / solid nature, grey, other vcolours possible | |
| 3. Product properties Form / condition Colour Odour | Rods, sheets, profiles / solid nature, grey, other vcolours possible odourless | |
| 3. Product properties Form / condition Colour Odour Density | Rods, sheets, profiles / solid nature, grey, other vcolours possible odourless 0,90 – 1,0 g/cm ³ | |
| 3. Product properties Form / condition Colour Odour Density Melting temperature | Rods, sheets, profiles / solid nature, grey, other vcolours possible odourless 0,90 – 1,0 g/cm ³ 130 – 170 °C | |
| 3. Product properties Form / condition Colour Odour Density Melting temperature Thermal decomposition | Rods, sheets, profiles / solid nature, grey, other vcolours possible odourless $0,90 - 1,0 \text{ g/cm}^3$ $130 - 170 \ ^{\circ}\text{C}$ ca. 300 \ ^{\circ}\text{C} | |



4. Handling and storage

| Machining | The product can be machined with standard machinery and tools. Before machining the product should be stored at room temperature 24 h. Reinforced products with glass fibers (round rods from 80mm and plates from 50mm thick) should be preheated before sawing or drilling. We recommend heating the materials to 90-120 ° C at a heating / cooling rate of approx. 10 ° C / h. Evacuate swarf to prevent slipping or tripping. Observe the maximum allowable concentration of dust levels on the working area which apply in your country. Wear safety goggles during machining. General dust limit value: Respirable dust (6 mg/m ³); Inhalable dust (10 mg/m ³). | |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Storage | The products shall be stored indoor to keep away from any source of degradation such as sunlight, UV-jets, ionizing radiation, chemicals, | |
| Safety measures | the general industrial safety measures should be considered. A thermal damage during machining should be avoided. | |
| 5. Fire-fighting measures | | |
| Suitable extinguishing agents | Water spraying jet, foam, dry chemical, carbon dioxide (CO ₂). | |
| Potential combustion products | Carbon dioxide (CO ₂), carbon monoxide (CO). Formation of further decomposition and oxidation products depent upon the fire conditions. Under special fire conditions traces of other toxic substances are possible. | |
| Special protective equipment | Wear a self-contained breathing apparatus. | |
| Further information | Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. | |
| 6. Disposal considerations | | |
| European waste catalogue | According to the "European Waste Catalogue and Hazardous Waste List" uncontaminated waste from the products is not classi- fied as hazardous. Following code numbers can be used: 070213 waste plastic from manufacture, formulation, supply and use of plastics, 120105 plastic shavings and turnings 57129 other cured waste plastics (Austria) | |
| Waste disposal | If recycling is not possible, waste disposal by landfill or incineration in compliance with state and local regulations. The product do not contain pigments or stabilizers based on cad- mium. The product is not biologically degradable, but based on the present state of knowledge no negative effects on the environment may be anticipated. | |



7. Marking and guidelines

| Marking in accordance with EEC guidelines | Not subject to labelling |
|-------------------------------------------|--------------------------------------------------------------|
| Other guidelines | - |
| Transport regulations | Not classified as hazardous good under transport regulations |

8. Other information

According EG directive 1907/2006/EG (REACh), our products are clearly defined as articles, exempt from registration. The European regulation (EV) about chemicals, which came into force June 1st 2007, prescribes Material Safety Data Sheets (MSDS) only for dangerous substances and preparations. According REACh we are manufacturing articles and we are not required to issue MSDS.

All above mentioned information are based according to today's state of knowledge and supply no warranty of quality. Existing laws and regulations have to be observed by the recepient of our products on his own authority.

